MH239 Hall-effect sensor is a temperature stable, stress-resistant, Low Tolerance of Sensitivity nano-power switch. Superior high-temperature performance is made possible through a dynamic offset cancellation that utilizes chopper-stabilization. This method reduces the offset voltage normally caused by device over molding, temperature dependencies, and thermal stress.

MH239 is special made for low operation voltage, 1.65V, to active the chip which is includes the following on a single silicon chip: voltage regulator, Hall voltage generator, small-signal amplifier, chopper stabilization, Schmitt trigger, CMOS output driver. Advanced CMOS wafer fabrication processing is used to take advantage of low-voltage requirements, component matching, very low input-offset errors, and small component geometries.This device requires the presence of omni-polar magnetic fields for operation.

The package type is in a Halogen Free version has been verified by third party Lab.


Features and Benefits

- CMOS Hall IC Technology
- Strong RF noise protection
- 1.65 to 5.5V for battery-powered applications
- Omni polar, output switches with absolute value of North or South pole from magnet
- Operation down to 1.65V, Nano power consumption
- Ultra Low power consumption at 1.6uA (Avg)
- Multi Small Size option
- Low sensitivity drift in crossing of Temp. range
- High ESD Protection, HBM >±8KV(min)
- Totem-pole output
- RoHS compliant 2011/65/EU and Halogen Free.

Applications

- Solid state switch
- Handheld Wireless Handset Awake Switch (Flip Cell/PHS Phone/Note Book/Flip Video Set)
- Lid close sensor for battery powered devices
- Magnet proximity sensor for reed switch replacement in low duty cycle applications
- Water Meter
- Floating Meter
- PDVD
- NB

Ordering Information



Company Name and Product Category

MH:MST Hall Effect/MP:MST Power IC

Part number

181,182,183,184,185,248,249,276,477,381,381F,381R,382…..

If part # is just 3 digits, the fourth digit will be omitted.

Temperature range

E: 85 ℃, I: 105 ℃, K: 125 ℃, L: 150 ℃

Package type

UA:TO-92S,VK:TO-92S(4pin),VF:TO-92S(5pin),SO:SOT-23,

SQ:QFN-3,ST:TSOT-23,SN:SOT-553,SF:SOT-89(5pin),


SS:TSOT-26,SD:DFN-6； SA:Represents ATEC packaged TSOT-23.

Sorting

α,β,Blank…..

Part No.	**Temperature Suffix**	**Package Type**
MH239EUA	E (-40°C to + 85°C)	UA (TO-92S)
MH239ESO	E (-40°C to + 85°C)	SO (SOT-23)

Functional Diagram



***Note**: Static sensitive device; please observe ESD precautions. Reverse V_{DD} protection is not included. For reverse voltage protection, a 100 Ω resistor in series with V_{DD} is recommended.*

MH239, HBM >±8KV which is verified by third party lab.

Absolute Maximum Ratings *At(T_A=25℃)*

Characteristics	Values	Unit
Supply voltage,(V_{DD})	9	V
Output Voltage,(V_{out})	9	V
Reverse Voltage,(V_{DD}) (V_{OUT})	-0.5	V
Magnetic flux density	Unlimited	Gauss
Output current,(I_{OUT})	10	mA
Operating temperature range, (T_A)	-40 to +85	℃
Storage temperature range, (T_S)	-65 to +150	℃
Maximum Junction Temp,(T_j)	150	℃


Note: *Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute maximum-rated conditions for extended periods may affect device reliability.*

Electrical Specifications

DC Operating Parameters：T_A=25℃, V_{DD}=3.0V

Parameters	Test Conditions	Min	Typ	Max	Units
Supply Voltage,(V_{DD})	Operating	1.65		5.5	V
Supply Current,(I_{DD})	Awake State		0.7	1.0	mA
	Sleep State		0.3	1.0	μA
	Average		1.6		uA
Output Leakage Current,(*Ioff*)	Output off			1.0	uA
Output High Voltage,(V_{OH})	I_{OUT}=5mA(Source)	V_{DD}-0.04			V
Output Low Voltage,(V_{OL})	I_{OUT}=5mA(Sink)			0.04	V
Awake mode time,(*Taw*)	Operating		20	45	uS
Sleep mode time,(T_{SL})	Operating		20	45	mS
Electro-Static Discharge	HBM	8			kV

Typical Application Circuit



MH239EUA/SO Magnetic Specifications


DC Operating Parameters：T_A=25℃, V_{DD}=3.0V

Parameter	*Symbol*	*Test Conditions*	*Min.*	*Typ.*	*Max.*	*Units*
OperatingPoint	B_{OPS}	S pole to branded side, B > BOP, Vout On		45	55	Gauss
	B_{OPN}	N pole to branded side, B > BOP, Vout On	-55	-45		Gauss
Release Point	B_{RPS}	S pole to branded side, B < BRP, Vout Off	20	35		Gauss
	B_{RPN}	N pole to branded side, B < BRP, Vout Off		-35	-20	Gauss
Hysteresis	B_{HYS}	|BOPx - BRPx|		10		Gauss


MH239EUA/SO Output Behavior versus Magnetic Polarity

DC Operating Parameters ：T_A = -40 to 85℃, V_{DD}=1.65Vto 5.5V


Parameter	*Test condition*	*OUT(SO)*	*Test condition*	*OUT(UA)*
South pole	B<B_{OPN}	Low	B>B_{OPS}	Low
Null or weak magnetic field	B=0 or B < |BRP|	High	B=0 or B < |BRP|	High
North pole	B>B_{OPS}	Low	B<B_{OPN}	Low



UA Package




SO Package



Sensor Location, Package Dimension and Marking

UA Package (TO-92S)




NOTES:


1.Controlling dimension: mm
2.Leads must be free of flash and plating voids
3.Do not bend leads within 1 mm of lead to package interface.
4.PINOUT:

Pin 1	VDD
Pin 2	GND
Pin 3	Output


Hall Chip Location



Output Pin Assignment (Top view)




SO Package (SOT-23) (Top View)



NOTES:

1 PINOUT (See Top View at left :)
Pin 1 VDD； Pin 2 Output； Pin 3 GND
2 Controlling dimension: mm
3 Lead thickness after solder plating will be 0.254mm maximum
4 XX: Date Code, Refer to DC table

Hall Plate Chip Location



(For reference only)Land Pattern

